

VIDEO CONFERENCE PTZ CAMERA



LB-20U3HL



4K
60FPS



AI Humanoid
Tracking



Wide
Angle lens



Remote
Control



Multiple
Interfaces

Features:

- ◆ Zoom: 20X Optical Zoom
- ◆ 1080p-60FPS Video resolution
- ◆ 60.7 Degree field of view
- ◆ Remote Control
- ◆ Full HD
- ◆ ACC Audio Encoding
- ◆ AI Based Human Tracking
- ◆ USB C-Type HDMI, LAN, 3G-SDI

Product Specification

▼ Camera Spec

Signal System	HDMI : 4KP60, 4KP59.94, 4KP50, 4KP30, 4KP25, 4KP29.97, 1080P60, 1080P50, 1080I60, 1080I50, 1080P30, 1080P59.94, 1080I59.94, 1080P29.97, 720P60, 720P59.94 ; 3G-SDI : 1080P/60, 1080P/50, 1080P/30, 1080P/29.97, 1080P/59.94, 1080P/25; 1080I/60, 1080I/50, 1080I/59.94; 720P/60, 720P/59.94;
Scanning Mode	Progressive
Digital Zoom	16×
Minimum Illumination	0.5Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual, VAR
Backlight Compensation	Support
Digital Noise Reduction	3D Digital Noise Reduction
SNR	≥ 55dB
Pan Angle	±170°
Tilt Angle	-30° ~ +90°
Pan Speed	1.7° ~ 100° /s
Tilt Speed	1.7° ~ 69.9° /s
Image Flip	Support
Image Freeze	Support
PoE+	Support
Preset Position	255
Preset Accuracy	0.1°
▼ I/O	
HD Output	1 x HDMI: Version 2.0; 1 x 3G-SDI: BNC , 800mVp-p, 75Ω, as per SMPTE 424M standard
Network Interface	1 x RJ45: 10M/100M/1000M adaptive Ethernet
Audio Interface	1 x LINE IN: 3.5mm Jack 1 x LINE OUT: 3.5mm Jack
USB Interface	1 x USB2.0,Type-A (Support Host or Device mode)

Control Interface	1 x RS485: 2pin phoenix port, Max Distance: 1200m, Protocol: VISCA / Pelco-D / Pelco-P; 1 x RS232 IN: 8pin Mini DIN, Max Distance: 30m, Protocol: VISCA / Pelco-D / Pelco-P; 1 x RS232 OUT: 8pin Mini DIN, Max Distance: 30m, Protocol: VISCA only
Restore Button	Support
Power Interface	JEITA type (DC IN 12V)

▼ Network Spec

Video Compression	H.265 / H.264 / MJPEG
Video Stream	First Stream, Second Stream
First Stream Resolution	3840x2160, 1920x1080, 1280x720 etc.
Second Stream Resolution	720x480, 320x240 etc.
Video Bit Rate	First Stream: 32kbps~51200kbps Second Stream: 32kbps~20480kbps
Bit Rate Control	VBR, CBR
Frame Rate	50Hz: 1fps~50fps, 60Hz:1fps~60fps
Audio Compression	AAC、G711A
Audio Bit Rate	96Kbps , 128Kbps
Protocols	NDI® HX2,SRT,TCP/IP, HTTP, RTSP, RTMP(s), Onvif,DHCP,GB/T 28181,Multicast, etc.

▼ USB Spec

Operating System Supported	Windows 7 (only supports UVC1.1 features), Windows 8 and above version, Mac OS X, Linux 2.4.6 and above version, Android needs to include the version of UVC-related drivers
Color System / Compression	YUY2 / H.264 / MJPEG
Video Format	YUY2:Max.1080P5 ; H.264 AVC: Max.2160P30 ; MJPEG:Max. 2160P30
USB Audio	Support
USB Video Communication Protocol	UVC 1.1~1.5
UVC PTZ Control	Support



LOGIBIRD®

Simplify your Business